

INDIAN INSTITUTE OF SCIENCE EDUCATION AND RESEARCH PUNE

CLARIFICATION ON TENDER NUMBER - IISER/PUR/2263/20

ITEM DESCRIPTION- PROCUREMENT OF SERVER

Refer IISER Pune Global tender notice dated 05/10/2021 for procurement of server

Pre-Bid meeting was held on October 14th, 2021 at 3.00 PM via video conferencing and minutes of meeting is as under.

At the outset, the Chairman welcomed all the Members and the representative of the Prospective Bidders and briefed in general the scope of the Project and thereafter requested Assistant Registrar (S&P) to brief the vendors on the salient features of the commercial terms and the indenting Officer to read out the clarification sought by the Prospective Bidders and replied thereto as detailed in Annexure.

The representatives present were satisfied with the replies given and it was informed that the corrections / additions / clarifications given, as discussed during the Pre-Bid Conference would be hosted on the website of IISER Pune and all the Prospective Bidders are required to take cognizance of the proceedings of the Pre-Bid Conference before submitting their bids as stipulated in the Bidding Documents.

The other terms & conditions of the notice issued on our IISER website www.iiserpune.ac .in will remain unchanged. No more correspondence in this regard will be entertained.

The meeting ended with vote of thanks to the Chair.

Sd/-

14.10.2021 Assistant Registrar (S&P)

Date: 14th October, 2021



IISER PUNE

TECHNICAL QUERIES AND CLARIFICATIONS

TENDER NUMBER - IISER/PUR/2263/20

Sr. No.	Query/Clarification Sought	Clarification / Amendment
1	Server Management: Server OEM, Server Management Software with rack mount accessories. 1U/2U or 3U may be quoted - We request IISER, Pune to allow 4U form factor along with 1U,2U and 3U	This is acceptable. 4U form factor under server management maybe quoted
2	CPU: 2 x Intel Xeon Gold 6230 @2.1 GHz / 20 Core or higher. -We request IISER, Pune to allow AMD EPYC 7352 @ 2.3 GHz / 24 Core Processor along with Intel Processor. Which complies to technical requirement as per RFP.	This is acceptable, change in tender will be made under CPU to state: 2 x Intel Xeon Gold 6230 @2.1 GHz / 20 Core or higher, or equivalent/better



Detailed specifications REVISED:

No Item		led specification	J 1(E) 13ED.	_
CPU equivalent/better Intel C621 Series Chipset OEM Motherboard or higher, or equivalent/better Memory 256 GB (32GB x 8) DDR4 RDIMM 2933MT/s GPU Quadro RTX 8000, or equivalent/better DIMM Slots 24 number of DIMM slots Memory Advanced ECC with multi-bit error protection, Online spare, mirrored memory and fast fault tolerance OS Drives 2*800 GB for OS along with 4* 1.9 TB SSD Drive Bays Expandable to 16 SFF hard disk drive bays Optical Drive Combo DVD-RW Internal/external Drive Controller M.2 drives Hardware RAID 20/1/5/6 support Remote Dedicated remote management controller with at least 4GB Flash memory 3-4 USB, 1Gb 4-port network adaptors, at least 3 PCI 3.0 expansion slots 10G NIC ports 10GBaseT 2-port Ethernet adaptor FC HBA Dual 16 Gbps FC HBA with cables Power Supply 750 watt Platinum Grade, Hot plug, redundant, power Supplies Redundant hot-plug system fans, minimum 6 or higher number fans Server OEM, Server Management Software with rack mount accessories.	Sr	la a sa	Due donat Connections	
CPU equivalent/better Intel C621 Series Chipset OEM Motherboard or higher, or equivalent/better Memory 256 GB (32GB x 8) DDR4 RDIMM 2933MT/s GPU Quadro RTX 8000, or equivalent/better DIMM Slots 24 number of DIMM slots Memory Advanced ECC with multi-bit error protection, Online spare, mirrored memory and fast fault tolerance OS Drives 2*800 GB for OS along with 4* 1.9 TB SSD Drive Bays Expandable to 16 SFF hard disk drive bays Optical Drive Combo DVD-RW Internal/external Drive On-board RAID controller supporting SSD/HDD and at least two M.2 drives Hardware RAID 12Gb/s SAS Raid Controller with at least 2GB Cache with RAID Controller 0/1/5/6 support 1 Remote Dedicated remote management controller with at least 4GB Flash memory 3-4 USB, 1Gb 4-port network adaptors, at least 3 PCI 3.0 expansion slots 10G NIC ports 10GBaseT 2-port Ethernet adaptor FC HBA Dual 16 Gbps FC HBA with cables Power Supply 750 watt Platinum Grade, Hot plug, redundant, power Supplies Redundant hot-plug system fans, minimum 6 or higher number fans Server OEM, Server Management Software with rack mount accessories.	no	item	•	
Intel C621 Series Chipset OEM Motherboard or higher, or equivalent/better Memory 256 GB (32GB x 8) DDR4 RDIMM 2933MT/s GPU Quadro RTX 8000, or equivalent/better DIMM Slots 24 number of DIMM slots Memory Advanced ECC with multi-bit error protection, Online spare, Protection mirrored memory and fast fault tolerance OS Drives 2*800 GB for OS along with 4* 1.9 TB SSD Drive Bays Expandable to 16 SFF hard disk drive bays Optical Drive Combo DVD-RW Internal/external Drive On-board RAID controller supporting SSD/HDD and at least two Controller M.2 drives Hardware RAID 12Gb/s SAS Raid Controller with at least 2GB Cache with RAID controller o/1/5/6 support Remote Dedicated remote management controller with at least 4GB Flash memory 3-4 USB, 1Gb 4-port network adaptors, at least 3 PCI 3.0 Ports expansion slots 10G NIC ports 10GBaseT 2-port Ethernet adaptor FC HBA Dual 16 Gbps FC HBA with cables Power Supply 750 watt Platinum Grade, Hot plug, redundant, power Supplies Redundant hot-plug system fans, minimum 6 or higher number fans Server OEM, Server Management Software with rack mount accessories.		CDU	, , , , , , , , , , , , , , , , , , ,	
Motherboard equivalent/better Memory 256 GB (32GB x 8) DDR4 RDIMM 2933MT/s GPU Quadro RTX 8000, or equivalent/better DIMM Slots 24 number of DIMM slots Memory Advanced ECC with multi-bit error protection, Online spare, mirrored memory and fast fault tolerance OS Drives 2*800 GB for OS along with 4* 1.9 TB SSD Drive Bays Expandable to 16 SFF hard disk drive bays Optical Drive Combo DVD-RW Internal/external Drive On-board RAID controller supporting SSD/HDD and at least two M.2 drives Hardware RAID 12Gb/s SAS Raid Controller with at least 2GB Cache with RAID Controller 0/1/5/6 support Remote Dedicated remote management controller with at least 4GB Management Flash memory 3-4 USB, 1Gb 4-port network adaptors, at least 3 PCI 3.0 expansion slots 10G NIC ports 10GBaseT 2-port Ethernet adaptor FC HBA Dual 16 Gbps FC HBA with cables Power Supply 750 watt Platinum Grade, Hot plug, redundant, power Supplies Redundant hot-plug system fans, minimum 6 or higher number fans Server OEM, Server Management Software with rack mount accessories.		CPU		_
Memory 256 GB (32GB x 8) DDR4 RDIMM 2933MT/s GPU Quadro RTX 8000, or equivalent/better DIMM Slots 24 number of DIMM slots Memory Advanced ECC with multi-bit error protection, Online spare, mirrored memory and fast fault tolerance OS Drives 2*800 GB for OS along with 4* 1.9 TB SSD Drive Bays Expandable to 16 SFF hard disk drive bays Optical Drive Combo DVD-RW Internal/external Drive On-board RAID controller supporting SSD/HDD and at least two M.2 drives Hardware RAID 12Gb/s SAS Raid Controller with at least 2GB Cache with RAID Controller 0/1/5/6 support Remote Dedicated remote management controller with at least 4GB Flash memory 3-4 USB, 1Gb 4-port network adaptors, at least 3 PCI 3.0 expansion slots 10G NIC ports 10GBaseT 2-port Ethernet adaptor FC HBA Dual 16 Gbps FC HBA with cables Power Supply 750 watt Platinum Grade, Hot plug, redundant, power Supplies Redundant hot-plug system fans, minimum 6 or higher number fans Server OEM, Server Management Software with rack mount accessories.			•	
GPU Quadro RTX 8000, or equivalent/better DIMM Slots 24 number of DIMM slots Memory Advanced ECC with multi-bit error protection, Online spare, mirrored memory and fast fault tolerance OS Drives 2*800 GB for OS along with 4* 1.9 TB SSD Drive Bays Expandable to 16 SFF hard disk drive bays Optical Drive Combo DVD-RW Internal/external Drive On-board RAID controller supporting SSD/HDD and at least two M.2 drives Hardware RAID 12Gb/s SAS Raid Controller with at least 2GB Cache with RAID Controller 0/1/5/6 support Remote Dedicated remote management controller with at least 4GB Flash memory 3-4 USB, 1Gb 4-port network adaptors, at least 3 PCI 3.0 expansion slots 10G NIC ports 10GBaseT 2-port Ethernet adaptor FC HBA Dual 16 Gbps FC HBA with cables Power Supply 750 watt Platinum Grade, Hot plug, redundant, power Supplies Redundant hot-plug system fans, minimum 6 or higher number fans Server OEM, Server Management Software with rack mount accessories.				_
DIMM Slots 24 number of DIMM slots Memory Advanced ECC with multi-bit error protection, Online spare, mirrored memory and fast fault tolerance OS Drives 2*800 GB for OS along with 4* 1.9 TB SSD Drive Bays Expandable to 16 SFF hard disk drive bays Optical Drive Combo DVD-RW Internal/external Drive On-board RAID controller supporting SSD/HDD and at least two M.2 drives Hardware RAID Controller Remote Management Dedicated remote management controller with at least 4GB Flash memory 3-4 USB, 1Gb 4-port network adaptors, at least 3 PCI 3.0 expansion slots 10G NIC ports 10GBaseT 2-port Ethernet adaptor FC HBA Dual 16 Gbps FC HBA with cables Power Supply 750 watt Platinum Grade, Hot plug, redundant, power Supplies Redundant hot-plug system fans, minimum 6 or higher number fans Server OEM, Server Management Software with rack mount accessories.		_		
Memory Protection OS Drives OS Drives Drives Drive Bays Optical Drive Combo DVD-RW Internal/external Drive On-board RAID controller supporting SSD/HDD and at least two M.2 drives Hardware RAID Controller Remote Management Management Dedicated remote management controller with at least 4GB Management Flash memory 3-4 USB, 1Gb 4-port network adaptors, at least 3 PCI 3.0 expansion slots 10G NIC ports FC HBA Dual 16 Gbps FC HBA with cables Power Supply Fans Server OS Drives Advanced ECC with multi-bit error protection, Online spare, mirrored memory and fast fault tolerance 2*800 GB for OS along with 4* 1.9 TB SSD Duly B SSD Drive Bays Optical Drive On-board RAID controller supporting SSD/HDD and at least two M.2 drives Hardware RAID Ontroller O/1/5/6 support Remote Dedicated remote management controller with at least 4GB Flash memory 3-4 USB, 1Gb 4-port network adaptors, at least 3 PCI 3.0 expansion slots 10G NIC ports FC HBA Dual 16 Gbps FC HBA with cables Power Supply Fans Server OEM, Server Management Software with rack mount accessories.				
Protection mirrored memory and fast fault tolerance OS Drives 2*800 GB for OS along with 4* 1.9 TB SSD Drive Bays Expandable to 16 SFF hard disk drive bays Optical Drive Combo DVD-RW Internal/external Drive On-board RAID controller supporting SSD/HDD and at least two M.2 drives Hardware RAID 12Gb/s SAS Raid Controller with at least 2GB Cache with RAID Controller 0/1/5/6 support Remote Dedicated remote management controller with at least 4GB Flash memory 3-4 USB, 1Gb 4-port network adaptors, at least 3 PCI 3.0 Ports expansion slots 10G NIC ports 10GBaseT 2-port Ethernet adaptor FC HBA Dual 16 Gbps FC HBA with cables Power Supply 750 watt Platinum Grade, Hot plug, redundant, power Supplies Redundant hot-plug system fans, minimum 6 or higher number fans Server OEM, Server Management Software with rack mount accessories.		DIMM Slots	24 number of DIMM slots	
Protection mirrored memory and fast fault tolerance OS Drives 2*800 GB for OS along with 4* 1.9 TB SSD Drive Bays Expandable to 16 SFF hard disk drive bays Optical Drive Combo DVD-RW Internal/external Drive On-board RAID controller supporting SSD/HDD and at least two M.2 drives Hardware RAID 12Gb/s SAS Raid Controller with at least 2GB Cache with RAID Controller 0/1/5/6 support Remote Dedicated remote management controller with at least 4GB Flash memory 3-4 USB, 1Gb 4-port network adaptors, at least 3 PCI 3.0 Ports expansion slots 10G NIC ports 10GBaseT 2-port Ethernet adaptor FC HBA Dual 16 Gbps FC HBA with cables Power Supply 750 watt Platinum Grade, Hot plug, redundant, power Supplies Redundant hot-plug system fans, minimum 6 or higher number fans Server OEM, Server Management Software with rack mount accessories.		Memory	Advanced ECC with multi-bit error protection, Online spare,	
OS Drives 2*800 GB for OS along with 4* 1.9 TB SSD Drive Bays Expandable to 16 SFF hard disk drive bays Optical Drive Combo DVD-RW Internal/external Drive On-board RAID controller supporting SSD/HDD and at least two M.2 drives Hardware RAID 12Gb/s SAS Raid Controller with at least 2GB Cache with RAID Controller 0/1/5/6 support Remote Dedicated remote management controller with at least 4GB Flash memory 3-4 USB, 1Gb 4-port network adaptors, at least 3 PCI 3.0 expansion slots 10G NIC ports 10GBaseT 2-port Ethernet adaptor FC HBA Dual 16 Gbps FC HBA with cables Power Supply 750 watt Platinum Grade, Hot plug, redundant, power Supplies Redundant hot-plug system fans, minimum 6 or higher number fans Server OEM, Server Management Software with rack mount accessories.		Protection	mirrored memory and fast fault tolerance	
Drive Bays Expandable to 16 SFF hard disk drive bays Optical Drive Combo DVD-RW Internal/external Drive On-board RAID controller supporting SSD/HDD and at least two M.2 drives Hardware RAID 12Gb/s SAS Raid Controller with at least 2GB Cache with RAID Controller 0/1/5/6 support Remote Dedicated remote management controller with at least 4GB Flash memory 3-4 USB, 1Gb 4-port network adaptors, at least 3 PCI 3.0 expansion slots 10G NIC ports 10GBaseT 2-port Ethernet adaptor FC HBA Dual 16 Gbps FC HBA with cables Power Supply 750 watt Platinum Grade, Hot plug, redundant, power Supplies Redundant hot-plug system fans, minimum 6 or higher number fans Server OEM, Server Management Software with rack mount accessories.		OS Drives	,	
Optical Drive Combo DVD-RW Internal/external Drive On-board RAID controller supporting SSD/HDD and at least two M.2 drives Hardware RAID 12Gb/s SAS Raid Controller with at least 2GB Cache with RAID Controller 0/1/5/6 support Remote Dedicated remote management controller with at least 4GB Flash memory 3-4 USB, 1Gb 4-port network adaptors, at least 3 PCI 3.0 expansion slots 10G NIC ports 10GBaseT 2-port Ethernet adaptor FC HBA Dual 16 Gbps FC HBA with cables Power Supply 750 watt Platinum Grade, Hot plug, redundant, power Supplies Redundant hot-plug system fans, minimum 6 or higher number fans Server OEM, Server Management Software with rack mount accessories.		Drive Bays	Expandable to 16 SFF hard disk drive bays	
On-board RAID controller supporting SSD/HDD and at least two M.2 drives Hardware RAID Controller 12Gb/s SAS Raid Controller with at least 2GB Cache with RAID O/1/5/6 support Remote Management Dedicated remote management controller with at least 4GB Flash memory 3-4 USB, 1Gb 4-port network adaptors, at least 3 PCI 3.0 expansion slots 10G NIC ports 10GBaseT 2-port Ethernet adaptor FC HBA Dual 16 Gbps FC HBA with cables Power Supply 750 watt Platinum Grade, Hot plug, redundant, power Supplies Redundant hot-plug system fans, minimum 6 or higher number fans Server OEM, Server Management Software with rack mount accessories.				
Controller M.2 drives Hardware RAID 12Gb/s SAS Raid Controller with at least 2GB Cache with RAID 0/1/5/6 support Remote Dedicated remote management controller with at least 4GB Flash memory 3-4 USB, 1Gb 4-port network adaptors, at least 3 PCI 3.0 expansion slots 10G NIC ports 10GBaseT 2-port Ethernet adaptor FC HBA Dual 16 Gbps FC HBA with cables Power Supply 750 watt Platinum Grade, Hot plug, redundant, power Supplies Redundant hot-plug system fans, minimum 6 or higher number fans Server OEM, Server Management Software with rack mount accessories.			On-board RAID controller supporting SSD/HDD and at least two	
Controller 0/1/5/6 support Remote Dedicated remote management controller with at least 4GB Management Flash memory 3-4 USB, 1Gb 4-port network adaptors, at least 3 PCI 3.0 Ports expansion slots 10G NIC ports 10GBaseT 2-port Ethernet adaptor FC HBA Dual 16 Gbps FC HBA with cables Power Supply 750 watt Platinum Grade, Hot plug, redundant, power Supplies Redundant hot-plug system fans, minimum 6 or higher number fans Server OEM, Server Management Software with rack mount accessories.		Controller		
Controller 0/1/5/6 support Remote Dedicated remote management controller with at least 4GB Management Flash memory 3-4 USB, 1Gb 4-port network adaptors, at least 3 PCI 3.0 expansion slots 10G NIC ports 10GBaseT 2-port Ethernet adaptor FC HBA Dual 16 Gbps FC HBA with cables Power Supply 750 watt Platinum Grade, Hot plug, redundant, power Supplies Redundant hot-plug system fans, minimum 6 or higher number fans Server OEM, Server Management Software with rack mount accessories.		Hardware RAID	12Gb/s SAS Raid Controller with at least 2GB Cache with RAID	
Remote Management Bedicated remote management controller with at least 4GB Nos Nos Nos Remote Management Bedicated remote management controller with at least 4GB Flash memory 3-4 USB, 1Gb 4-port network adaptors, at least 3 PCI 3.0 expansion slots 10G NIC ports 10GBaseT 2-port Ethernet adaptor FC HBA Dual 16 Gbps FC HBA with cables Power Supply 750 watt Platinum Grade, Hot plug, redundant, power Supplies Redundant hot-plug system fans, minimum 6 or higher number fans Server OEM, Server Management Software with rack mount accessories.		Controller	0/1/5/6 support	2
Management Flash memory 3-4 USB, 1Gb 4-port network adaptors, at least 3 PCI 3.0 Ports expansion slots 10G NIC ports 10GBaseT 2-port Ethernet adaptor FC HBA Dual 16 Gbps FC HBA with cables Power Supply 750 watt Platinum Grade, Hot plug, redundant, power Supplies Redundant hot-plug system fans, minimum 6 or higher number fans Server OEM, Server Management Software with rack mount Server accessories.	1	Remote		_
3-4 USB, 1Gb 4-port network adaptors, at least 3 PCI 3.0 Ports expansion slots 10G NIC ports 10GBaseT 2-port Ethernet adaptor FC HBA Dual 16 Gbps FC HBA with cables Power Supply 750 watt Platinum Grade, Hot plug, redundant, power Supplies Redundant hot-plug system fans, minimum 6 or higher number fans Server OEM, Server Management Software with rack mount accessories.		Management		1405
Ports expansion slots 10G NIC ports 10GBaseT 2-port Ethernet adaptor FC HBA Dual 16 Gbps FC HBA with cables Power Supply 750 watt Platinum Grade, Hot plug, redundant, power Supplies Redundant hot-plug system fans, minimum 6 or higher number fans Server OEM, Server Management Software with rack mount accessories.			,	
FC HBA Dual 16 Gbps FC HBA with cables Power Supply 750 watt Platinum Grade, Hot plug, redundant, power Supplies Redundant hot-plug system fans, minimum 6 or higher number fans Fans Server OEM, Server Management Software with rack mount accessories.		Ports	, , , , , , , , , , , , , , , , , , , ,	
FC HBA Dual 16 Gbps FC HBA with cables Power Supply 750 watt Platinum Grade, Hot plug, redundant, power Supplies Redundant hot-plug system fans, minimum 6 or higher number fans Fans Server OEM, Server Management Software with rack mount accessories.		10G NIC ports	10GBaseT 2-port Ethernet adaptor	
Power Supply 750 watt Platinum Grade, Hot plug, redundant, power Supplies Redundant hot-plug system fans, minimum 6 or higher number fans Fans Server OEM, Server Management Software with rack mount accessories.				
Redundant hot-plug system fans, minimum 6 or higher number fans Fans Server OEM, Server Management Software with rack mount accessories.		Power Supply	•	
Fans fans Server OEM, Server Management Software with rack mount accessories.		11,		
Server accessories.		Fans		
Server accessories.			Server OEM, Server Management Software with rack mount	
		Server		
Management 10/20 or 30 or 40 may be quoted		Management	1U/2U or 3U or 4U may be quoted	
5yrs comprehensive warranty onsite (inclusive), 24X7, 4 hrs			, ,	1
Warranty response time				
Ubuntu 18.04 Aug. LTS rel. Onsite installation, configuration,		•	Ubuntu 18.04 Aug. LTS rel. Onsite installation, configuration,	1
and testing				
OS along with two server in HA configuration for load balancing		OS	along with two server in HA configuration for load balancing	